

## C.C.Components Pty Ltd

### PVC Cleating, Sidewalls & Tracking Strips

FPI 6802WT050EN is a white non-toxic flexible PVC compound formulated for the extrusion of Conveyor Belting Cleats, Sidewalls & Tracking Strips. Our range of Cleats, Sidewalls & Tracking Strips provide excellent extraction resistance, flexibility, animal & mineral oil resistance & welding properties to PVC & PU belting. Other colours are available against minimum order quantities.

The values indicated are approximates and should be used as a guide only.

Type	Base Width MM	Overall Height MM	Minimum Pulley Diam. MM	Approx Roll Length MTS
<b>T Cleating</b>				
20mm	24	20	100	30
25mm	31	25	100	30
38mm	31	38	130	30
50mm	31	50	150	30
75mm	35	75	180	25
<b>75° Super Scoop Cleating</b>				
50mm	31	50	150	30
75mm	35	75	180	25
<b>20mm Tube Top Cleating</b>				
40mm	32	40	150	30
60mm	34	60	180	30
<b>Sidewall</b>				
25mm	50	25	63	30
38mm	50	38	95	30
50mm	50	50	125	30
75mm	50	75	190	30
<b>Notched Tracking Strip</b>				
M	11	6	50	200
A	13	8	75	150
B	15	12	90	100
<b>Solid Tracking Strip</b>				
K	8	5		200
M	11	6	60	200
A	13	8	80	150
B	15	12	110	100
C	22	15	150	50